



EN

Operating and usage instructions for the TM series watch winder

- 1) Clamp the watch on the watchband
- 2) plug the adapter into the back of the device/insert AA batteries (2pcs) - then plug into a wall outlet
- 3) switch the switch on the back of the device to position I - on
- 4) select one of the 4 winding modes by turning the switch

position 1 -OFF - none of the winding modes is set.

Position 2 - 2 minutes of clockwise rotation - 13 minutes pause - then the cycle repeats for 12 hours. For the next 12 hours the unit is in a resting state – TPD 900

Position 3 - 2 minutes of counterclockwise rotation - 13 minutes of pause - then the cycle repeats for 12 hours. For the next 12 hours the machine is at rest – TPD 900

Position 4 - 2 minutes clockwise rotation - 18 minutes pause, 2 minutes counterclockwise rotation - 13 minutes pause - then the cycle repeats for 12 hours. For the next 12 hours the machine is in a resting state – TPD 650

Position 5 - 4 minutes clockwise rotation - 28 minutes pause, 4 minutes anti-clockwise rotation - 28 minutes pause - then the cycle repeats for 12 hours. For the next 12 hours the machine is in a resting state – TPD 900

SAFETY INSTRUCTIONS

- always check that the power cord is intact before use
- if the power cord is damaged, do not plug the adapter into a power outlet
- do not stop the moving carrier
- do not rotate the cord when the unit is switched off
- do not use the device in damp or dusty environments
- do not expose the unit to direct sunlight for long periods of time
- do not expose the instrument to heat sources (radiators, stoves, heaters, etc.)
- when not using the device for a long period of time, always unplug the cable from the socket and remove the batteries

